По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72 Астана +7(7172)727-132 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89 Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395) 279-98-46

Киргизия (996)312-96-26-47

Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)65-04-62 Киров (8332)68-02-04 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Курск (4712)77-13-04 Липецк (4742)52-20-81 Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Нижний Новгород (831)429-08-12 Казахстан (772)734-952-31 Новокузнецк (3843)20-46-81 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Пермь (342)205-81-47 Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Симферополь (3652)67-13-56 Таджикистан (992)427-82-92-69 Смоленск (4812)29-41-54 Сочи (862)225-72-31 Ставрополь (8652)20-65-13 Сургут (3462)77-98-35 Тверь (4822)63-31-35 Томск (3822)98-41-53 Тула (4872)74-02-29 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Ярославль (4852)69-52-93

Эл. почта bwo@nt-rt.ru || Сайт: https://bawoo.nt-rt.ru/



Skid steer loader



Bawoo Company Corp

"In the name of BAWOO COMPANY, there are quality and satisfaction by continuous technical development"

We have been focusing on the substantial growth than the outward expansion of the company and concentrating on small construction machinery line with our accumulated technique and various hands-on experiences. It made us the professional manufacturer specializing in skid steer loader.

BAWOO COMPANY's line of products combine high performance with exceptional durability and quality. One of our advantage is products according to customer's needs and continuous improvement of quality. We are small but we have tons of potentiality for the future and enough technology. Our freedom allows us to concentrate on developing the latest technologies into our equipment. We have been looking for the best way in order to increase your productivity at the toughest environment.

We will continue to work hard to earn our customer's trust and satisfaction.





02/03

BSL Series

BSL330

The new standard for productive comfort and speed on the site. New line up, vertical lift loader arms provide long reach, maximum lifting and dumping capacity at full lift height. The new BSL series skid loader is the outcome of Bavoo's superior innovation and product development. BSL series are built for more aggressive tasks.

These are just some of the features that come standard when you buy Bawoo.

Spacious cab give you excellent leg room.

Functional operator's room gives you all-day comfort and it must increase your productivity. You'll experience the highest level of design, comfortable operator's room and exceptional performance on BSL series. NOW ENJOY YOUR WORKS with BSL series! A few common features are:

- Lift arm provides more height and longer reach. It is acheived at a truck loading and unloading heights
- An enhanced chassis provides superior weight distribution and stability
- New single-plane vertical-lift, robust lift arm

More tractive power, You can push more and dig harder.

New deluxe canopy

DIMENSION	BSL330
Power output / rpm (C)74HP/2500rpm	or (K)84.5HP/2600rpm
Rated Operating Capacity	1,050kg
Operating Weight	3,350kg



BSL Series

BSL350 / BSL400

BSL series is with new feature of ergonomic designed new cab. Operation, maintenance and machine designed is greatly enhanced.

Standard joystick controls allow you to control all machine functions with your hands. Fingertip controls make all operation comfortable and accurate. New features keep you running longer, increase your uptime.

DIMENSION	BSL350	BSL400
Power output / rpm	(C)74HP/2500rpm or	100HP/2600rpm
	(K)84.5HP/2600rpm	
Rated Operating Capacity	1,200kg	1,430kg
Operating Weight	3,570kg	3,775kg





BSL EX Series

BSL350EX / BSL400EX

Telescopic boom-UNIQUE ITEM for skid loader Innivative product development and unique EX model are bawoo core competencies.

Unique Telescopic model as optional item. Telescopic boom offer greater vertical outreach than other models. You can experience the new dump reach as well as dump geight with telescopic boom. It's right model for higher working height. BAWOO telescopic boom are engineered for the toughestcommercial, residential and landscaping applications.



DIMENSION	BSL350EX	BSL400EX
Power output / rpm	(C)74HP/2500rpm or (K)84.5HP/2600rpm	100HP/2600rpm
Rated Operating Capa	city 1,200kg(880kg)	1,430kg(920kg)
Operating Weight	3,990kg	4,195kg
Dump Height	3,255mm	3,385mm



V Series

VJ57/VJ67

VJ series are ideal for taking pallets or bricks off a truck and placing them around the jobsite and its good for loading a lot of dirt into a dump truck.

Its designed for capacity, lift height and a better balance. V series are a great all-around skid steer loader, from paving to loading and more.

V series are designed for long & stable operation in the toughest applications and they combine the best performance advantages into one machine, the superior reach and lift capacity along with unmached stability.

V series are smooth, quiet and very efficent.

DIMENSION	VJ57	VJ67
Power output / rpm	53HP/2500rpm	64HP/2600rpm
Rated Operating Capacity	950kg	1,020kg
Operating Weight	2,830kg	2,970kg







J Series

J57/J67

J series will give you the power and control to get the job done right. J series features redesigned cab with a standard suspension seat and improved service ability.

Joystick controls allow you to control all machine functions with your hands. Fingertip controls make all operation comfortable and accurate.

The detent feature continously engages hydraulic flow without needing to hold the switch.

J series gives you more than enough power and convenience to perform high productivity loading duties without any fatigue. Travel by left joystick control and operation of bucket and lift arm by right joystick control.

DIMENSION	J57	J67
Power output / rpm	53HP/2500rpm	65HP/2600rpm
Rated Operating Capacity	850kg	910kg
Operating Weight	2,780kg	2,890kg









M Series

M50/720

For particular purpose of skid steer loader at tight area A compact but highly effective by a narrow width, High dump height and powerfull performance. M50 features a compact size for many inside tasks that requiring maximum handling power and maneuverability in a confined space.

DIMENSION	M50	720
Power output / rpm	53HP/2500rpm	53HP/2500rpm
Rated Operating Capacity	680kg	720kg
Operating Weight	2,290kg	2,320kg





BTL Series

BTL300/BTL350

Experience the difference of BTL series now.

You must meet exceptional power, performance and versatility.

Compact track loader BTL is the right solution, When you deal with jobs demanding power and traction. BTL series offers large operator's area with Pilot joystick control system, permanently lubricated idlers and rollers, excellent traction and flotation by wide track, right mounting undercarriage, ground clearance for travel over rough terrian.

Excellent vertical lift path that is perfect for truck loading and material handling applications due to the increase in height and reach.

Also delivers greater lift capacity for efficiency in repeated load and carry operation.

Greater fuel capacity offers longer operating shifts and more productivity. Spend less downtime refueling.



DIMENSION	BTL300	BTL350	
		(C)74HP/2500rpm	
Power output / rpm	84.5HP/2600rpm	or (K)84.5HP/2600rpm	
Rated Operating Capacit	y 1,250kg	1,350kg	
Operating Weight	3,850kg	4,250kg	





BTL Series

BTL400

Ideal loader path for heavy duty attachments and ground engaging applications. Designed for space, safety and comfort with ROPS/FOPS and large emergency exit. Increased flexibility on handle more jobs with just one machine. Increased stability on steep grades and rough terrains, maximum power from the driveline to the ground providing higher traction, lower ground pressure. Increased cooling capacity for better performance and longer machine life. New features keep you running longer, increase your uptime and make it eaasier to do routine maintenance. Protected engine room door from obstacles, scrapes and bumps on the worksite.

DIMENSION		BTL400	
Power output / rpm (C)74HP/2500rpm or		or (K)84.5HP/2600rpm	
Rated Operating Capacity		1,320kg	
Operating Weight		4,230kg	





BTL Series

BTL400EX

BTL400EX is the only compact track loader with a telescopic boom. Its designed to lift higher, to reach further and to dig deeper. Telescopic boom is unique item and innovative product development. Maximized workability. Enhanced durability & reliablity.

DIMENSION	BTL400EX
Power output / rpm	(C)74HP/2500rpm or (K)84.5HP/2600rpm
Rated Operating Capac	tity 1,320kg(930kg)
Operating Weight	4,650kg





Attachments



4 in 1 bucket

 Needed just one attachment to do so many things at once. It is ideal for grappling, dozing, backfilling, loading, digging and fine grading.



Fork

 Handle materials easier and move materials faster with the utility fork attachment. The strong teeth handle a variety of farm and ranch chores easily and efficiently.



High dump bucket

- Reach new heights with your current skid steer loader.
 With the high-dump bucket you can increase your dumping height.
- High Dump Bucket is an essential attachment in the poultry business. With the extra dumping height, you can easily load dump trucks to capacity. Bawoo high dump bucket has extra tall sides, to make your clean up job get done faster.



Screen bucket

 Screen bucket is excellent for picking up rocks and leaving excess dirt or sand behind from work areas can be cultivated or landscaped.



Backhoe

- Transforms skid steer loader into a powerful mini-excavator
- Backhoe are designed for high productive digging and smooth operation.
- Cost-effective and convenient for rental dealers, landscaping, nurseries, sewage system and water and power line contractors, and electrical contractors.



Tooth bucket

- Skid steer loader bucket with teeth. Tooth bucket is ideal for light-duty grading and leveling applications as well as material handling.
- . It offer good bucket breakout force and capacity.





Compactor

- High impulse energy for greater compaction.
- It is very useful in strengthening an incline and helping to strengthen the basis of soil, aggregate and sand after the road construction work.
- Perfect and strong compacting.
- To harden the ground and the slope.
- Water works and sewer construction, reclamation of the gas pipe, cable and wire, repair work on asphalt etc.

Auger

- Auger is used for digging vertical holes, even though the loader is working on uneven terrain.
- Digga premium drilling augers are designed for drilling and augering in most ground conditions.
- The innovative design allows the gearbox to go down the hole to maximise drilling depth without extentions.



Breaker

- Breaker provides high-impact forces for vertical and horizontal breaking concrete, rock, pavement and other demolition project.
- Lower maintenance, with a boltless mounting system
- A high quality, modern hammer
- · Lower sound power levels.

12/13

GET more functions!

Various attachments fill needs in agriculture, construction, landscaping, industrial, mining and waste applications.

Largest variety of attachments adds greater versatility to your skid steer loaders. All loaders are equipped with universal quick coupler system for easy installation of various attachments and concealed aux. hydraulic lines for protection of hoses. Not only BAWOO offers the various range of skid steer loader with performance but also BAWOO offers more attachments to improve your models. Having the right tools is key to any job.

BAWOO skid steer loaders can be competent for shoveling, lifting, excavating, drilling, cleaning work with different attachments.





Bale handler • Useful for round or square bales • Slide from min. 430mm to max. 1460mm



Grapple

(Fork grapple, utility Bucket grapple)

- Grapple handle loose or bulky landscaping or farming materials like straw, rugged barryard manure.
- Cut down on daily hand chores and free up your time, perform a wide variety of job functions.
- Grapple is ideal for handling scrap, waste or pipe.
- This grapple allows easy handling of a variety of hard-to-manage materials
- in the industrial setting or construction site. It's built strong for tough working conditions





Pallet fork

 Move bulky, bagged or palletized materials quickly and easily.
 Adjustable forks load and unload, lift and carry, move and place materials in industrial plants and landscaping.



Sweeper

- Sweepers is the right choice for today's clean-up needs.
- Sweeps loose materials while loader moves forward and cleans surface of debris or snow.
- Sweeps parking lots, warehouse, docks, etc. and cleans up construction sites.
- Sweep, collects and dump debris to the bucket and then empty bucket.



Tree spade

Dig and transplant trees with the speed and efficiency of the tree spade attachment.

Dig, transplant, and package trees without leaving the comfort of the operator's seat.

The rugged, dependable tree spade attachment turns your loader into a transplanting unit.

It is the ideal attachment for matket applications such as nurseries, landscapers, golf courses, construction, farming, rental yards, parks and municipalities.



Rear stabilizer

Rear mount stabilizers are used to provide stability to the rear of most skid steer loaders.

It works great to put the force of skid steer where it needs to be. They are designed to be used in combination with backhoe or tree spade. You are ready to get the most digging force from skid steer backhoe or tree spade.



Snow blade/dozer blade

- Our blades are commercial quality and heavy duty.
 Whether clearing snow in the winter or grading in the summer,
- the snow blade works to easily move and discard materials. • Excellent blade visibility and maneuverability makes any
- Excellent blade visibility and maneuverability makes a removal job quick and easy.
- Materials flow away easily with the rolled moldboard design.
 Prevent sparks and surface gouges with rubber and poly
- cutting edges available.



Track over wheel

- Easy installation to tires in less than 30 minutes
- Improve performance in rough, rocky, and muddy conditions with steel tracks.
- Steel track over wheels provide better flotation and reduced ground pressure, protection of tires from wear and damage.

Options

There are many options for customer's convenience and higher performance, Bawoo offers a variety of important accessories that can be installed easily on elther new or used equipment. These can help upgrade an existing unit or customize one for a particular job.



Closed cabin









High flow system



Two-speed travel



Self leveling system



Hydraulic quick tach



Counter weight

Bawoo Company





Foot pedal



Rotating beacon



Direction Indicator



Power supply



15 Double accelerator

Digital instrument panel

Backup camera

Features

All Bawoo loaders brings a long list of innovative features and class-leading performance.



Operator station

The cab features certified safety ROPS & FOPS, a spacious operator's room. Technically advanced instrument panels at right and left side provides a super view in all directions and easy notice in condition of loader. Operator restraint system will protect you. All skid loaders are equipped with a hydraulic automaticlocking system for operator's safety. Loader don't move as well as bucket & lift arm don't move when operator raise safety bar.

Operator can work at comfortable & quiet working condition. We applied insulation materials between operator's room and engine room for low cab noise.



Power and Durability

The superior versatility and design make SSL series an exceptional value for you

Long-running performances make SSL series the ideal skid steer loader for hard work in confined spaces.

A HARD WORKER, all our product lines are powered by a rugged diesel engine.

An energy-efficient power engine will deliver the performance you need.

Large hydraulic capacities and excellent cooling capacities make loader work easy.

Triple filtration system strain even tiny particles from the oil and keep the engine,

transmission and hydraulic system running for years.

High efficiency motor & pump and rugged engine system increase durability of loader.

A cutoff device of battery prevent discharging battery in a long period of storage.

All SSL series has been protected by an electro-deposited coating system, which completely seals each metallic component and offers a superlative degree of protection from damage and corrosion.



Serviceability

All skid steer loaders are designed for quick and easy serviceability. Full tilt ROPS & FOPS, easily removable rear door without tools provide the greatest access for daily service checks and routine maintenance. Operator can access to air cleaner, engine, pump and major components easily.



Specifications

Dimension		M50	720	J57	J67
Overall operating height (to top of bucket)	А	3,498mm	3,700mm	3,870mm	4,004mm
Overall operating height (to hinge pin)	В	2,629mm	2,840mm	2,970mm	3,102mm
Overall Height	С	1,700mm	1,889mm	1,970mm	2,013mm
Overall Length (with bucket)	D	3,143mm	3,148mm	3,270mm	3,373mm
Overall Length (without bucket)	E	2,445mm	2,425mm	2,560mm	2,672mm
Overall Width	F	1,240mm	1,490mm	1,690mm	1,810mm
Tread Width	G	990mm	1,204mm	1,330mm	1,402mm
Wheel Base	н	958mm	1,047mm	1,045mm	1,100mm
Ground Clearance	J	143mm	192mm	174mm	214mn
Dump Angle	к	35degree	43degree	42degree	42degree
Dump Height	L	1,981mm	2,094mm	2,236mm	2,364mm
Dump Reach	М	537mm	400mm	608mm	561mm
Rollback at ground	N	26degree	35degree	23degree	23degree
Turn circle front (without bucket)	٥	1,268mm	1,175mm	1,234mm	1,276mm
Turn circle front (with bucket)	R	1,915mm	1,855mm	1,958mm	2,070mm
Turn circle rear	S	1,348mm	1,436mm	1,490mm	1,557mm
Overall width (without bucket)	т	1,200mm	1,469mm	1,603mm	1,690mm
Departure angle	U	22degree	25degree	24degree	25.6degree
Performance		M50	720	J57	J67
Rated operating capacity		680kg	720kg	850kg	910kg
Tipping load		1,300kg	1,400kg	1,680kg	1,980kg
•		0.0001	100000000000	0 7001	0.0001

Operating weight 2,290kg 2,320kg 2,780kg 2,890 Travel speed 10.6km/h 11.8km/h 10.3km/h 11.4km Bucket capacity (heaped capacity) 0.29m³ 0.40m³ 0.40m³ 0.40m³ Drive 4WD 4WD 4WD 4WD 4WD 4WD Tire (or Track width for STL) 10*16.5 10*16.5 10*16.5 12*10 Power output 53HP 53HP 53HP 64					
Travel speed 10.6km/h 11.8km/h 10.3km/h 11.4km Bucket capacity (heaped capacity) 0.29m³ 0.40m³ 0.40m³ 0.40m³ 0.40m³ 0.40m³ Drive 4WD <	Tipping load	1,300kg	1,400kg	1,680kg	1,980kg
Bucket capacity (heaped capacity) 0.29m^3 0.40m^3 0.40m^3 0.40m^3 0.40m^3 Drive4WD4WD4WD4WD4WDTire (or Track width for STL)10*16.510*16.510*16.512*10Power output53HP53HP53HP64	Operating weight	2,290kg	2,320kg	2,780kg	2,890kg
Drive4WD4WD4WD4WD4WDTire (or Track width for STL)10*16.510*16.510*16.512*10Power output53HP53HP53HP64	Travel speed	10.6km/h	11.8km/h	10.3km/h	11.4km/h
Tire (or Track width for STL) 10*16.5 10*16.5 10*16.5 12*10 Power output 53HP 53HP 53HP 64	Bucket capacity (heaped capacity)	0.29m³	0.40 m ³	0.40 m ³	0.45m³
Power output 53HP 53HP 64	Drive	4WD	4WD	4WD	4WD
	Tire (or Track width for STL)	10*16.5	10*16.5	10*16.5	12*16.5
/ rpm /2500rpm /2500rpm /2500rpm /2500rpm	Power output	53HP	53HP	53HP	64HP
	/ rpm	/2500rpm	/2500rpm	/2500rpm	/2500rpm

Sp	ecif	icat	ions

EX	BSL400	BSL400	BSL350EX	BSL350	BSL330	VJ67	VJ57
nm	4,962r	4,962mm	4,861mm	4,861mm	3,880mm	3,871mm	3,848mm
hm	4,046r	3,385mm	3,945mm	3,258mm	2,962mm	2,980mm	2,955mm
nm	2,092r	2,092mm	2,057mm	2,057mm	2,064mm	2,057mm	2,032mm
nm	3,585r	3,585mm	3,473mm	3,473mm	3,520mm	3,300mm	3,300mm
hm	2,863r	2,863mm	2,571mm	2,571mm	2,586mm	2,586mm	2,586mm
۱m	1,886r	1,886mm	1,886mm	1,886mm	1,810mm	1,810mm	1,690mm
۱m	1,476r	1,476mm	1,502mm	1,502mm	1,388mm	1,384mm	1,343mm
۱m	1,216r	1,216mm	1,181mm	1,181mm	1,178mm	1,045mm	1,045mm
nm	205r	205mm	195mm	195mm	211mm	209mm	184mm
ee	37deg	37degree	36degree	36degree	41degree	41degree	41degree
nm	3,385r	2,620mm	3,255mm	2,588mm	2,300mm	2,245mm	2,234mm
nm	965r	515mm	920mm	567mm	851mm	854mm	901mm
ee	27deg	27degree	27degree	27degree	26degree	26degree	26degree
۱m	1,325r	1,325mm	1,330mm	1,330mm	1,288mm	1,246mm	1,246mm
۱m	2,096r	2,096mm	2,116mm	2,116mm	2,047mm	2,036mm	2,011mm
nm	1,727r	1,727mm	1,606mm	1,606mm	1,214mm	1,504mm	1,504mm
۱m	1,800r	1,800mm	1,800mm	1,800mm	1,696mm	1,696mm	1,613mm
ee	15deg	15degree	25.5degree	25.5degree	16degree	25degree	23degree
EX	BSL40	BSL400	BSL350EX	BSL350	BSL330	VJ67	VJ57
(g)	1,430kg(920	1,430kg	1,200kg(880kg)	1,200kg	1,050kg	1,020kg	950kg
kg	3,01	3,010kg	2,720kg	2,720kg	2,210kg	2,050kg	1,974kg
kg	4,19	3,775kg	3,990kg	3,570kg	3,350kg	2,970kg	2,830kg
γh)	12.5km/h(18.0kr	12.5km/h(18.0km/h)	10.9km/h	10.9km/h	11.4km/h	10.5km/h	10.8km/h







,					1000 AND 200	Charles and
12.5km/h(18.0km/h)	12.5km/h(18.0km/h)	10.9km/h	10.9km/h	11.4km/h	10.5km/h	10.8km/h
0.5m3	0.5 m³	0.5 m³	0.5 m³	0.45 m³	0.45 m³	0.40 m ³
4WD	4WD	4WD	4WD	4WD	4WD	4WD
12*16.5	12*16.5	12*16.5	12*16.5	12*16.5	12*16.5	10*16.5
100HP	100HP		04 5115 0 0000	7410 00500	64HP	53HP
/2600rpm	/2600rpm	rpm	or 84.5HP@2600ŋ	74HP@2500rpm (/2500rpm	/2500rpm

* Specification and design are subject to change without notice.

18/19

Specifications

Dimension		BTL330	BTL350	BTL400	BTL400EX
Overall operating height (to top of bucket)	А	3,860mm	4,184mm	4,236mm	4,923mm
Overall operating height (to hinge pin)	в	2,980mm	3,240mm	3,288mm	3,975mm
Overall Height	с	2,160mm	2,068mm	2,084mm	2,084mm
Overall Length (with bucket)	D	3,370mm	3,476mm	3,571mm	3,571mm
Overall Length (without bucket)	E	2,682mm	2,752mm	2,830mm	2,830mm
Overall Width	F	1,810mm	1,886mm	1,886mm	1,886mm
Track gauge	G	1,330mm	1,400mm	1,582mm	1,582mm
Length of track on ground	н	1,480mm	1,485mm	1,619mm	1,619mm
Ground Clearance	J	230mm	244mm	240mm	240mm
Dump Angle	к	43degree	43degree	37degree	37degree
Dump Height	L	2,230mm	2,482mm	2,595mm	3,281mm
Dump Reach	Μ	970mm	779mm	569mm	980mm
Rollback at ground	Ν	26degree	31degree	27degree	27degree
Turn circle front (without bucket)	٥	1,100mm	1,350mm	1,427mm	1,427mm
Turn circle front (with bucket)	R	2,197mm	2,215mm	2,243mm	2,243mm
Turn circle rear	S	1,480mm	1,543mm	1,617mm	1,617mm
Overall width (without bucket)	т	1,650mm	1,850mm	1,929mm	1,929mm
Departure angle	U	41degree	34degree	34degree	34degree
		DTI 220	DTI 250	PTI 400	DTI 400EV

Performance	BTL330	BTL350	BTL400	BTL400EX	
Rated operating capacity	1,250kg	1,350kg	1,320kg	1,320kg(930kg)	
Tipping load	2,550kg	2,700kg	2,640kg	2,640kg	
Operating weight	3,850kg	4,250kg	4,230kg	4,650kg	
Travel speed	10.5km/h	10.5km/h	10.8km/h	10.8km/h	
Bucket capacity (heaped capacity)	0.43 m ³	0.5 m³	0.5 m³	0.5 m³	
Drive		Rubber crawler type			
Tire (or Track width for STL)	320mm	450mm	400mm	400mm	
Power output / rpm	84.5HP@2600rpm	(C)74HP/2500rpm or (K)84.5HP/2600rpm			



Radial lift path(EX)





* Specification and design are subject to change without notice.

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72 Астана +7(7172)727-132 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89 Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395) 279-98-46 Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)65-04-62 Киров (8332)68-02-04 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Курск (4712)77-13-04 Липецк (4742)52-20-81 Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Нижний Новгород (831)429-08-12 Казахстан (772)734-952-31 Новокузнецк (3843)20-46-81 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Пермь (342)205-81-47 Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Симферополь (3652)67-13-56 Таджикистан (992)427-82-92-69 Смоленск (4812)29-41-54 Сочи (862)225-72-31 Ставрополь (8652)20-65-13 Сургут (3462)77-98-35 Тверь (4822)63-31-35 Томск (3822)98-41-53 Тула (4872)74-02-29 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Эл. почта bwo@nt-rt.ru || Сайт: https://bawoo.nt-rt.ru/